

SET-UP SHEET

X4F'27 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'27

RACE			
TRACK			
NAME		DATE	
COUNTRY		CITY	

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAP TIME	LAPS	TIME
			/sec		/

TRACK		
TRACK SURFACE	☐ CARPET	☐ ASPHALT
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED ☐ FAST
TRACTION	☐ LOW	☐ MEDIUM ☐ HIGH

TRANSMISSION		
GEAR DIFFERENTIAL - OIL	/cSt	DIFFERENTIAL POSITION UP ☐ DOWN ☐
PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
		BEARING HOLDER KIT ☐ ☐ ALU

FRONT	SHOCKS	REAR
	XRAY SPRINGS	
	OIL /cSt	
	REBOUND %	
☐ 4 HOLES ☐ PSS	1.1mm 1.2mm	1.1mm 1.2mm 4 HOLES PSS
SHOCK LENGTH	/mm	SHOCK LENGTH

ANTI-ROLL BAR	
THICKNESS/mm	THICKNESS/mm

TIRES	
ADDITIVE	
ADDITIVE TIMING	
WIPE OFF TIME	
TIRE WARMERS	
Timing:	Temp.:
FRONT TIRES ADDITIVE AREA	

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT %	REAR %
--------------	----	----------------	---------	--------

MOTOR	TIMING	RPM LIMIT
ESC	BATTERIES	
BODY	WING	

	BODY POSITION
	WING SIDE PLATE YES ☐ NO ☐

FRONT REINFORCEMENT	TOP DECK FLEX	REAR REINFORCEMENT	TOP DECK CUTTING
---------------------	---------------	--------------------	------------------

FRONT ARMS	CHASSIS	REAR ARMS
MEDIUM ☐ HARD ☐ SHORT ☐	GRAPHITE ☐ ALU 1.5 ☐	MEDIUM ☐ HARD ☐ SHORT ☐

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER 5° 4° 3° Adjust with eccentric bushings	REAR CASTER 0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings
Upper links CASTER BUMP STEER /mm HEIGHT /mm SHIM /mm	Upper links CASTER TOE GAIN /mm RIDE HEIGHT /mm
FF /mm FR /mm SERVO SAVER ☐ SERVO HORN ☐	RF /mm RR /mm RIDE HEIGHT /mm

FRONT	
CAMBER /deg. Left=Right BODY STOP YES ☐ NO ☐ SHIM /mm PLAY /mm #107712 DOWNSTOP /mm Set with shocks ☐ Set without shocks ☐	FF /mm FR /mm SHIMS /mm DRIVE SHAFT 58mm 59mm SHIM /mm DROOP /mm #107730 Droop Gauge SUSPENSION FLEX SCREW YES ☐ NO ☐ YES ☐ NO ☐

REAR	
CAMBER /deg. Left=Right SHIM /mm PLAY /mm #107712 DOWNSTOP /mm Set with shocks ☐ Set without shocks ☐	RF /mm RR /mm SHIMS /mm SHIM /mm DROOP /mm SUSPENSION FLEX SCREW YES ☐ NO ☐ YES ☐ NO ☐

FRONT TOP VIEW		REAR	
TOE OUT Left=Right BUMPER WEIGHT YES ☐ NO ☐ UPPER CLAMP KIT ☐ -1mm SHIMS /mm UPPER CLAMP FLEX FRONT UPPER CFF™ ARM ☐ LINK SHORT ☐ LINK LONG ☐ HUB OFFSET ☐ ☐ ☐ SHIM /mm	TOE IN Left=Right ARS LINKS POSITION UPPER CLAMP FLEX CHASSIS FLEX NO BRACE ☐ MEDIUM ☐ STIFF ☐ HUB OFFSET ☐ ☐ ☐ SHIM /mm	REAR UPPER CFF™ ARM ☐ LINK SHORT ☐ LINK LONG ☐	ACKERMANN BUSHINGS

FRONT BOTTOM VIEW		REAR	
WEIGHT LEFT & RIGHT YES ☐ NO ☐ STEER. LOCK /deg. FRONT BRACE MOTOR MOUNT #293085 TUNGSTEN WEIGHT 10g FRONT ARMS MEDIUM ☐ HARD ☐ SHORT ☐	CHASSIS GRAPHITE ☐ ALU 1.5 ☐	T-BRACE ALU ☐ BRASS ☐	REAR ARMS MEDIUM ☐ HARD ☐ SHORT ☐

reset all