


■ CELL CHARACTERISTICS

Capacity	Typical	3000 mAh 10.8 Wh
	Minimum	2900 mAh 10.4 Wh
Cell Voltage	Nominal	3.6 V
	Charge	4.2 V
	Discharge	2.5 V
Charge Current	Standard	3 A
	Maximum	9 A (70°C cut-off)
Charge Time	Standard	1.5 hr
Discharge Current	Maximum	36 A (80°C cut-off)
Temperature	Charge	0°C to 60°C
	Discharge	-40°C to 60°C
Energy Density	Volumetric	631Wh/l
	Gravimetric	234 Wh/kg
Typical Impedance	AC (30%SOC)	8 mΩ
	DC (50%SOC)	17 mΩ

■ PHYSICAL CHARACTERISTICS



Shape	Cylindrical
Can	Steel
Diameter	18.6 mm (Max)
Height	65.2 mm (Max)
Weight	47 g (Max)

The information contained herein is for reference only and does not imply a performance guarantee or a product warranty. Specifications and characteristics are subject to change without prior notice. This product is not designed or produced for use in any vape or e-cigarette devices.


For application specific information, please contact E-One Moli Energy Sales and Applications or the nearest MOLICEL® recognized agent.
Version 1.1

■ Taiwan Facility
10 Dali 2nd Rd., Shan-Hwa,
Tainan City, Taiwan, R.O.C.
Tel: 886-6-505-0666
Fax: 886-6-505-0777
Mail to: service@molice.com
<http://www.molice.com>


■ Canada Facility
20 000 Stewart Crescent
Maple Ridge, BC, Canada, V2X 9E7
Tel: 1-604-466-6654
Fax: 1-604-466-6600
Mail to: molice@molienrgv.com
<http://www.molice.com>

■ Headquarters
10F, 113, Sec.2, Zhong Shan N Rd.,
Taipei, Taiwan, R.O.C.
Tel: 886-2-2567-3500
Fax: 886-2-2567-6500
Mail to: service@molice.com
<http://www.molice.com>


■ Charge Characteristics



■ Discharge Rate Characteristics



■ Discharge Rate Characteristics



■ Cycle Characteristics

