G.T.POWER

CHARGER COMPARISON CHART

AC/DC	SKU	SRP	Max Charge Current (A)	Watts / Ch (AC)	Watts / Ch (DC)	Channels	Max Cell Count	Bluetooth (App)	LiPo	Lilon	LiHV	LiFe	NIMH	Pb	SSLB*	Touch Screen	IR Testing	Storage	Discharge
PD606	GTP0146	£45.99	6	50	50	1-6	6x1S / 3x2S / 2x3S		✔			✔							
C6D	GTP0006	£46.99	6	50	50	1	15 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔			✔	✔	✔
C6D Air	GTP0184	£49.99	12	100	300	1	15 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔	✔		✔	✔	✔
X2 Mini	GTP0171	£68.99	10	50***	100	2	8 NiXX / 4 LiXX		✔	✔	✔	✔	✔	✔					
C6D Pro	GTP0174	£68.99	12	100	300	1	15 NiXX / 6 LiXX	✔	✔	✔	✔	✔	✔	✔			✔	✔	✔
V6	GTP0168	£75.99	14	100	200	1	16 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔			✔	✔	✔
X4 Mini	GTP0169	£79.99	10	25**	100	4	8 NiXX / 4 LiXX		✔	✔	✔	✔	✔	✔					
TD610 Pro	GTP0153	£87.99	10	100	100	1	14 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔		✔	✔	✔	✔
X2	GTP0148	£94.99	7	80	80	2	15 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔			✔	✔	✔
X2 Air	GTP0185	£99.99	12	100	200	2	15 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔	✔		✔	✔	✔
X2 Pro	GTP0178	£124.99	12	100	200	2	15 NiXX / 6 LiXX	✔	✔	✔	✔	✔	✔	✔			✔	✔	✔
X4	GTP0149	£179.99	7	100	100	4	15 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔			✔	✔	✔
DC	**SKU**	**SRP**	**Max Charge Current (A)**	**Watts / Ch (AC)**	**Watts / Ch (DC)**	**Channels**	**Max Cell Count**	**Bluetooth (App)**	**LiPo**	**Lilon**	**LiHV**	**LiFe**	**NIMH**	**Pb**	**SSLB***	**Touch Screen**	**IR Testing**	**Storage**	**Discharge**
V6	GTP0154	£58.99	16	-	300	1	16 NiXX / 6 LiXX		✔	✔	✔	✔	✔	✔			✔	✔	✔
AC	**SKU**	**SRP**	**Max Charge Current (A)**	**Watts / Ch (AC)**	**Watts / Ch (DC)**	**Channels**	**Max Cell Count**	**Bluetooth (App)**	**LiPo**	**Lilon**	**LiHV**	**LiFe**	**NIMH**	**Pb**	**SSLB***	**Touch Screen**	**IR Testing**	**Storage**	**Discharge**
A3	GTP0056	£13.99	0.9	20	-	1	3 LiXX		✔										
N802	GTP0116	£13.99	2	20	-	1	8 NiXX						✔						
SD4	GTP0120	£28.99	3	20	-	1	8 NiXX / 4 LiXX		✔		✔	✔	✔						
SD4 III	GTP0166	£33.99	4	50	-	1	8 NiXX / 4 LiXX		✔		✔	✔	✔						
SD6	GTP0145	£37.99	6	50	-	1	10 NiXX / 6 LiXX		✔		✔	✔	✔						
C6D Mini	GTP0158	£46.99	10	100	-	1	8 NiXX / 4 LiXX		✔	✔	✔	✔	✔	✔			✔	✔	✔

* SSLB = Solid State Lithium Battery = Enhanced safety. Higher energy storage. Wide operating temperture range.
**For the X4 Mini the maximum AC wattage 'pool' of 100W is shared dynamically across the chanels in use. If all 4 channels are in use, each receives 25W. When charging only one battery, the channel receives the full 100W.
***For the X2 Mini the maximum AC wattage 'pool' of 100W is shared dynamically across the chanels in use. If both channels are in use, each receives 50W. When charging only one battery, the channel receives the full 100W.

© 2026 J. Perkins (Distribution) Limited. Last updated 9th November 2026 - Rev 2.0